**ASTM E3022** ISO 3059 **RRES 90061 NADCAP** AITM6-1001

**ASTM E3022 ASTM E1444** 

CrackCheck

## **Spirit Series**

Portable LED UV Lamp

# Explosion-proof Certified Supreme Handy and Light

100% Conformance to Prime Standards

Spirit Series Handheld LED UV Lamp (ST-30) utilizes the state-of-art LED technology, as well as its intrinsically safe mechanical and electrical design, making it a perfect tool for inspection conditions with explosion-proof requirement. Spirit is popular for its explosion proof capability and supreme light and handy design for fluorescent inspection. Safety and portability is the spirit for Spirit Series UV LED Lamp.

Two models are available: ST-30 Battery and ST-30 Mains. Both models consist of 2 high performance UV LEDs and 1 white light LED.









Explosion-proof



Light & Handy



Safety Spectrum



White and **UV** Light



Anti-EMI




**Economical** 





Shanghai CHiNDT Systems and Services Co., Ltd. ISO9001 ( €







Tel: 86-21-39901501 🖨 E-mail: crackcheck@chindt.com



## **About Spirit**

Spirit Series handheld LED UV lamp utilizes the state-of-art LED technology and makes it a great tool for fluorescent MT, PT and leak detection. Two versions are available: battery version and mains version ST-30. Both versions consist of 2 UV LEDs and 1 white LED. Spirit is famous for its certified explosion proof capabilities and super light design.



### **Spirit Features**

- Compliance with all international standards and regulations, e.g. ASTM E3022, RRES 90061, AITM6-1001
- Explosion proof certified per EU Directives
- Super light and handy design
- White light and UV light are easily switchable
- Power Supply: Battery(ST-30B) or Mains(ST-30M)
- 100% solid state circuit ensuring working steadily in strong magnetic field
- Safe and pure UV-A spectrum in the range of 365-370nm with no UV-B and UV-C


### A Complete Spirit Package



## Spirit Data Sheet

Item	Spirit Mains	Spirit Battery
Model	ST-30M (Mains Version)	ST-30B (Battery Version)
Part Number	605003	605004
LED Source	2 UV-LEDs, 1 white light LED	
Wavelength	Certified 365-370nm	
UVA Intensity at 15"(380mm)	~ 4,000 uw/cm <sup>2</sup>	
Coverage Area at 15"(380mm)	>1000uw/cm²: ~Ф160mm	
Compliance	ASTM E 3022, ISO 3059, RRES 90061, NADCAP, AITM6-1001	
UVB /UVC	0	
Visible Light	< 5Lux (0.5 ft-candle)	
Dimension	82mm*112mm*200mm	
Weight	ca. 550g (1.2lb) without batteries ca. 640g (1.5lb) with batteries	
Operating Voltage	12V DC	
Power Supply	100-240V AC, 50/60Hz for mains version 2 * 3.7V lithium batteries (Type 18650) for battery version	
Running Time	~3 hours	
Battery Life	~1,000 charging cycles	

#### **Spirit Mounting Methods**





Mounting with spring balance and hook



#### **Spirit Certification**



#### **Accessories & Protection**

